

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

**SECTION 1: Identification of the substance/mixture and of the company/ undertaking****1.1 Product identifier**

Lithofin MN Colour Intensifier

**1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses**

Mixture Impregnation, Contains: organic solvents

**1.3 Details of the supplier of the safety data sheet**

**Supplier :** Lithofin AG  
**Street :** Heinrich-Otto-Str. 36  
**Postal code/City :** 73240 Wendlingen  
**Country :** GERMANY  
**Telephone :** +49 7024 9403 0  
**Telefax :** +49 7024 9403 40  
**Contact :** Technical Department  
**E-mail :** info@lithofin.de

**Emergency telephone number :** +49 7024 9403 0  
(Only available during office hours)

**1.4 Emergency telephone number**

see section 1.3

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP]**

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

**Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**Remark**

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

**2.2 Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]****Hazard pictograms**

Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

**Signal word**

Danger

**Hazard components for labelling**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Colour Intensifier

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

ETHYLBENZENE ; CAS No. : 100-41-4

### Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local and national regulations.

### Other labelling

#### 2.3 Other hazards

##### Adverse physicochemical effects

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

##### Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 2.4 Additional information

see section 12.5

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

XYLENE ; REACH No. : 01-2119488216-32-xxxx ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction :  $\geq 30 - < 35$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; REACH No. : 01-2119463258-33-xxxx ; EC No. : 919-857-5; CAS No. : (64742-48-9)

Weight fraction :  $\geq 25 - < 30$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 EUH066

Hydrocarbons, C9, aromatics ; REACH No. : 01-2119455851-35-xxxx ; EC No. : 918-668-5; CAS No. : (64742-95-6)

Weight fraction :  $\geq 15 - < 20$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411 EUH066

ETHYLBENZENE ; REACH No. : 01-2119489370-35 ; EC No. : 202-849-4; CAS No. : 100-41-4

Weight fraction :  $\geq 5 - < 10$  %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 (auditory organs) Acute Tox. 4 ; H332 Aquatic Chronic 3 ; H412

ETHYL ACETATE ; REACH No. : 01-2119475103-46-xxxx ; EC No. : 205-500-4; CAS No. : 141-78-6

Weight fraction :  $\geq 1 - < 5$  %

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

### Trade name : Lithofin MN Colour Intensifier

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 EUH066

TETRAETHYL SILICATE ; REACH No. : 01-2119496195-28-xxxx ; EC No. : 201-083-8; CAS No. : 78-10-4

Weight fraction :  $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

**Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH**

None (below the concentration limit)

**Contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH**

None (below the concentration limit)

#### Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

< 0,1% Benzene, Regulation (EC) No. 1272/2008, Annex VI; J, P

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice. Observe risk of aspiration if vomiting occurs.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

#### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

#### Following ingestion

Call a physician immediately. Keep at rest. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes for the doctor

Treat symptomatically.

#### Special treatment

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam Carbon dioxide (CO<sub>2</sub>) BC-powder ABC-powder Water spray jet

#### Unsuitable extinguishing media

Full water jet Strong water jet

### 5.2 Special hazards arising from the substance or mixture

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

**Hazardous combustion products**Carbon monoxide Carbon dioxide (CO<sub>2</sub>)**5.3 Advice for firefighters**

Use suitable breathing apparatus.

**Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**5.4 Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

**6.2 Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

**6.3 Methods and material for containment and cleaning up****For cleaning up**

Suitable material for taking up: Universal binder

Clean contaminated articles and floor according to the environmental legislation. Retain contaminated washing water and dispose it. Dispose of waste according to applicable legislation.

**6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

When using do not eat, drink, smoke, sniff.

**Protective measures**All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists  
Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.**Measures to prevent fire**

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of ignition - No smoking. The product is: Combustible

**Fire class :** B**Shake well before use** nein**Advices on general occupational hygiene**

P362+P364 - Take off contaminated clothing and wash it before reuse.

**7.2 Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep/Store only in original container. The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

**Hints on joint storage****Storage class (TRGS 510) :** 3**Protect from frost** nein**Recommended storage temperature** 5 - 25 °C

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

**Further information on storage conditions**

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

**7.3 Specific end use(s)****Recommendation**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limit values**

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : BAT ( D )

Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift

Limit value : 2 g/l

Version :

Limit value type (country of origin) : KZG ( D )

Limit value : 200 ppm / 870 mg/m<sup>3</sup>

Remark : H, B

Version :

Limit value type (country of origin) : MAK ( D )

Limit value : 100 ppm / 435 mg/m<sup>3</sup>

Remark : H, B

Version :

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 50 ppm / 220 mg/m<sup>3</sup>

Peak limitation : 2(II)

Remark : H

Version : 04.11.2017

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Xylene / Whole blood (B) / End of exposure or end of shift

Limit value : 1,5 mg/l

Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift

Limit value : 2 g/l

Version : 31.03.2004

Limit value type (country of origin) : STEL ( EC )

Limit value : 100 ppm / 442 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

Limit value type (country of origin) : TWA ( EC )

Limit value : 50 ppm / 221 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics ; CAS No. : (64742-48-9)

Limit value type (country of origin) : KZG ( D )

Limit value : 100 ppm / 600 mg/m<sup>3</sup>

Version :

Limit value type (country of origin) : MAK ( D )

Limit value : 50 ppm / 300 mg/m<sup>3</sup>

Version :

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 300 mg/m<sup>3</sup>

Peak limitation : 2(II)

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) :

5.2.1 (5.2.0)

Print date : 11.12.2023

---

Version :  
ETHYLBENZENE ; CAS No. : 100-41-4  
Limit value type (country of origin) : BAT ( D )  
Parameter : Urine (U) / End of exposure or end of shift  
Limit value : 600 mg/g Creatinine  
Version :  
Limit value type (country of origin) : KZG ( D )  
Limit value : 50 ppm / 220 mg/m<sup>3</sup>  
Remark : H, OL, B  
Version :  
Limit value type (country of origin) : MAK ( D )  
Limit value : 50 ppm / 220 mg/m<sup>3</sup>  
Remark : H, OL, B  
Version :  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 88 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H, Y  
Version : 23.06.2022  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift  
Limit value : 250 mg/g Creatinine  
Version : 25.02.2022  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
ETHYL ACETATE ; CAS No. : 141-78-6  
Limit value type (country of origin) : KZG ( D )  
Limit value : 400 ppm / 1460 mg/m<sup>3</sup>  
Remark : SSc  
Version :  
Limit value type (country of origin) : MAK ( D )  
Limit value : 200 ppm / 730 mg/m<sup>3</sup>  
Remark : SSc  
Version :  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 730 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 23.06.2022  
TETRAETHYL SILICATE ; CAS No. : 78-10-4  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 1,4 ppm / 12 mg/m<sup>3</sup>  
Peak limitation : 1(I)  
Version : 23.06.2022  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 44 mg/m<sup>3</sup> / 5 ppm  
Version : 20.06.2019

**DNEL-/PNEC-values****DNEL/DMEL**

XYLENE ; CAS No. : 1330-20-7

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) :

5.2.1 (5.2.0)

Print date : 11.12.2023

---

Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 108 mg/kg

Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 14,8 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 1,6 mg/kg

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 289 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 180 mg/kg

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 77 mg/m<sup>3</sup>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 125 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 125 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 185 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 208 mg/kg bw/day

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 871 mg/m<sup>3</sup>

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 32 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 11 mg/kg

Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 11 mg/kg

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 25 mg/kg

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 150 mg/m<sup>3</sup>

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 1,6 mg/kg/d

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 15 mg/m<sup>3</sup>

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 293 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 180 mg/kg/d

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 77 mg/m<sup>3</sup>

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 4,5 mg/kg/d

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 734 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 37 mg/kg/d

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 367 mg/m<sup>3</sup>

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 734 mg/m<sup>3</sup>

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 1468 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 1468 mg/m<sup>3</sup>



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 63 mg/kg/d  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 734 mg/m<sup>3</sup>

**TETRAETHYL SILICATE ; CAS No. : 78-10-4**

Limit value type : DNEL Consumer (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 25 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 25 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 8,4 mg/kg/d  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 8,4 mg/kg/d  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 25 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 25 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 85 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 85 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 12,1 mg/kg/d  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 12,1 mg/kg/d  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 85 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 85 mg/m<sup>3</sup>

**PNEC**

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) :

5.2.1 (5.2.0)

Print date : 11.12.2023

**XYLENE ; CAS No. : 1330-20-7**

Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,327 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	0,327 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,327 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	12,46 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Limit value :	12,46 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	6,58 mg/l

**ETHYLBENZENE ; CAS No. : 100-41-4**

Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,1 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,01 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	13,7 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Limit value :	1,37 mg/kg
Limit value type :	PNEC (Soil)
Limit value :	2,68 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	9,6 mg/l

**ETHYL ACETATE ; CAS No. : 141-78-6**

Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,24 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	1,65 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,024 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	1,15 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,115 mg/kg
Limit value type :	PNEC (Soil)
Limit value :	0,148 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	650 mg/l

**TETRAETHYL SILICATE ; CAS No. : 78-10-4**

Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,192 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,0192 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	0,18 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,018 mg/kg
Limit value type :	PNEC (Soil)
Limit value :	0,05 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	4000 mg/l

**8.2 Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation of the storage area.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 12.08.2022

**Version (Revision) :** 5.2.1 (5.2.0)

**Print date :** 11.12.2023

Technical measures and the application of suitable work processes have priority over personal protection equipment.

## Personal protection equipment

### Eye/face protection

#### Suitable eye protection

Eye glasses with side protection goggles

#### Required properties

EN 166

### Skin protection

#### Hand protection

**Suitable gloves type :** Gloves with long cuffs

**Suitable material :** Data apply to the main component. FKM (fluoro rubber), 0,7mm, >8h;

**Required properties :** EN ISO 374

**Recommended glove articles :** Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

**Additional hand protection measures :** Check leak tightness/impermeability prior to use.

**Remark :** Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

#### Body protection

Protective clothing.

**Suitable protective clothing :** Chemical protection clothing Chemical resistant safety shoes

**Required properties :** antistatic.

Protective clothing. : EN 13034 EN 14605

Chemical resistant safety shoes : EN ISO 20345

**Remark :** Barrier creams are not substitutes for body protection.

### Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

#### Suitable respiratory protection apparatus

Full-/half-/quarter-face masks (EN 136/140) Combination filtering device (EN 14387) ABEK-P1 (EN14387)

#### Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

### General information

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance :** Liquid

**Colour :** colourless

**Odour :** solvent

#### Safety characteristics

**Melting point/freezing point :** ( 1013 hPa ) < -18 °C

**Initial boiling point and boiling range :** ( 1013 hPa ) approx. 143 °C

**Decomposition temperature :** ( 1013 hPa ) not determined

**Flash point :** approx. 26 °C closed cup (EN ISO 3679)

**Auto-ignition temperature :** not determined

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Colour Intensifier

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

<b>Sustaining combustion</b>			Yes		UN Test L2:Sustained combustibility test
<b>Lower explosion limit :</b>			not determined		
<b>Upper explosion limit :</b>			not determined		
<b>Vapour pressure :</b>	( 50 °C )	<	3000	hPa	
<b>Density :</b>	( 20 °C )		0,86	g/cm <sup>3</sup>	Pyknometer (DIN EN ISO 2811-1)
<b>Solvent separation test :</b>	( 20 °C )	<	3	%	Test L1: Solvent separation test (UN)
<b>Water solubility</b>	( 20 °C )		hydrolysed		
<b>pH :</b>			not applicable		DIN 19268
<b>log P O/W :</b>			not determined		(Mixture)
<b>Flow time :</b>	( 23 °C )	approx.	14	s	ISO cup 4 mm (DIN EN ISO 2431)
<b>Odour threshold :</b>			not determined		
<b>Vapourisation rate :</b>			not determined		
<b>VOC content-EC</b>			87,4	Weight-%	*
<b>VOC content-EC</b>			747	g/l	*
<b>VOC-France</b>			A+		Décret no 2011-321 du 23 mars 2011

(\* VOC-EC = „Volatile organic compound (VOC)“ means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

## 9.2 Other information

Data apply to the main component:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS: 64742-48-9)

Lower explosion limit (Vol-%): 0,6

Upper explosion limit (Vol-%): 6,0

log P O/W: 5,0 - 6,7

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

### 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4 Conditions to avoid

Stable under recommended storage and handling conditions.

### 10.5 Incompatible materials

No data available

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Acute oral toxicity

Parameter :	LD50 ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Oral
Species :	Rat

**Trade name : Lithofin MN Colour Intensifier**

**Revision date :** 12.08.2022

**Version (Revision) :** 5.2.1 (5.2.0)

**Print date :** 11.12.2023

Effective dose : 8700 mg/kg  
 Parameter : LD50 ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )  
 Exposure route : Oral  
 Species : Rat  
 Effective dose : > 5000 mg/kg  
 Parameter : LD50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
 Exposure route : Oral  
 Species : Rat  
 Effective dose : > 2000 - 5000 mg/kg  
 Parameter : LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
 Exposure route : Oral  
 Species : Rat  
 Effective dose : 3500 mg/kg  
 Parameter : LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
 Exposure route : Oral  
 Species : Rat  
 Effective dose : 5600 mg/kg  
 Parameter : LD50 ( TETRAETHYL SILICATE ; CAS No. : 78-10-4 )  
 Exposure route : Oral  
 Species : Rat  
 Effective dose : > 2500 mg/kg  
 Method : OECD 423

**Acute dermal toxicity**

Parameter : LD50 ( XYLENE ; CAS No. : 1330-20-7 )  
 Exposure route : Dermal  
 Species : Rabbit  
 Effective dose : > 2000 mg/kg  
 Parameter : LD50 ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )  
 Exposure route : Dermal  
 Species : Rabbit  
 Effective dose : > 5000 mg/kg  
 Parameter : LD50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
 Exposure route : Dermal  
 Species : Rabbit  
 Effective dose : > 2000 mg/kg  
 Parameter : LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
 Exposure route : Dermal  
 Species : Rabbit  
 Effective dose : 15,4 mg/kg  
 Parameter : LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
 Exposure route : Dermal  
 Species : Rabbit  
 Effective dose : 18000 mg/kg

**Acute inhalation toxicity**

Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
 Exposure route : Inhalation  
 Species : Rat  
 Effective dose : 6350 mg/l  
 Parameter : LC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
 Exposure route : Inhalation  
 Species : Rat  
 Effective dose : 17,2 mg/l  
 Exposure time : 4 h  
 Parameter : LC50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
 Exposure route : Inhalation  
 Species : Rat

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

Effective dose :	58 mg/l
Exposure time :	8 h
Parameter :	LC50 ( TETRAETHYL SILICATE ; CAS No. : 78-10-4 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	10 mg/l
Exposure time :	4 h
Method :	OECD 403

**Specific effects (Longterm animal experiment)**

There are no data available on the preparation/mixture itself.

**Corrosion****Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**Repeated dose toxicity (subacute, subchronic, chronic)**

There are no data available on the preparation/mixture itself.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Carcinogenicity**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards**

No information available.

**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity**

Harmful to aquatic life with long lasting effects.

**Chronic (long-term) fish toxicity**

Parameter :	NOEC ( XYLENE ; CAS No. : 1330-20-7 )
Species :	Fish
Effective dose :	> 1 - 10 mg/l
Parameter :	NOEC ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Fish
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Fish
Effective dose :	> 9,65 mg/l
Exposure time :	32 D

**Chronic (long-term) toxicity to aquatic invertebrate**

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 12.08.2022

Version (Revision) :

5.2.1 (5.2.0)

Print date : 11.12.2023

Parameter :	NOEC ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Daphnia
Effective dose :	2,4 mg/l
Exposure time :	21 D

**Acute (short-term) toxicity to algae and cyanobacteria**

Parameter :	EC50 ( XYLENE ; CAS No. : 1330-20-7 )
Species :	Daphnia
Effective dose :	3,82 mg/l
Exposure time :	48 h
Parameter :	EC50 ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 1000 mg/l
Exposure time :	48 h
Method :	OECD 202
Parameter :	EC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )
Species :	Daphnia
Effective dose :	> 1 - 10 mg/l
Parameter :	EC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )
Species :	Daphnia
Effective dose :	2,4 mg/l
Exposure time :	48 h
Parameter :	EC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )
Species :	Algae
Effective dose :	4,6 mg/l
Exposure time :	72 h
Parameter :	EC50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Daphnia
Effective dose :	610 mg/l
Exposure time :	48 h
Parameter :	EC50 ( TETRAETHYL SILICATE ; CAS No. : 78-10-4 )
Species :	Daphnia
Effective dose :	> 75 mg/l
Exposure time :	48 h
Method :	OECD 202

**Chronic (long-term) toxicity to aquatic algae and cyanobacteria**

Parameter :	NOEC ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Algae
Effective dose :	> 100 mg/l
Exposure time :	72 h
Method :	OECD 201

**Sewage treatment plant**

Observe local regulations concerning effluent treatment.

**12.2 Persistence and degradability**

There are no data available on the preparation/mixture itself.

**Biodegradation**

There are no data available on the preparation/mixture itself.

**12.3 Bioaccumulative potential**

There are no data available on the preparation/mixture itself.

**12.4 Mobility in soil**

There are no data available on the preparation/mixture itself.

**12.5 Results of PBT and vPvB assessment**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 12.08.2022

**Version (Revision) :** 5.2.1 (5.2.0)

**Print date :** 11.12.2023

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Endocrine disrupting properties

No information available.

## 12.7 Other adverse effects

There are no data available on the preparation/mixture itself.

## 12.8 Additional ecotoxicological information

### Additional information

The product has not been tested.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of waste according to applicable legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

##### Waste codes/waste designations according to EWC/AVV

Waste code (EWC/AVV) : 07 01 04\* (other organic solvents, washing liquids and mother liquors)

##### After intended use

Do not allow to enter into surface water or drains. Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Delivery to an approved waste disposal company.

##### Disposal operations

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

##### Waste codes/waste designations according to EWC/AVV

Waste code packaging: 15 01 10\*

### 13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

## SECTION 14: Transport information

### 14.1 UN number or ID number

UN 1993

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · XYLENE)

#### Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · XYLENE)

#### Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · XYLENE)

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

**Class(es) :** 3  
**Classification code :** F1  
**Hazard identification number (Kemler No.) :** 30  
**Tunnel restriction code :** D/E  
**Special Provisions :** 640E · LQ 5 I · E 1  
**Hazard label(s) :** 3

#### Sea transport (IMDG)

**Class(es) :** 3  
**EmS-No. :** F-E / S-E  
**Special Provisions :** LQ 5 I · E 1



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Colour Intensifier

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

Hazard label(s) : 3  
Air transport (ICAO-TI / IATA-DGR)  
Class(es) : 3  
Special Provisions : E 1  
Hazard label(s) : 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

Land transport (ADR/RID) : No  
Sea transport (IMDG) : No  
Air transport (ICAO-TI / IATA-DGR) : No

### 14.6 Special precautions for user

None

### 14.7 Maritime transport in bulk according to IMO instruments

Not required.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)  
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures (clp)  
DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste (2000/532/EC)  
EN 2:1992 (DIN EN 2:2005-01)

#### Authorisations and/or restrictions on use

##### Restrictions on use

##### Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40, 75

##### Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### Other regulations (EU)

Regulation (EC) No. 648/2004 [Detergents regulation]  
Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

#### Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer

Not listed/not relevant.  
Contains the following substances that deplete the ozone layer: -

#### Regulation (EC) 2019/1021 [POP Regulation]

Not listed/not relevant.  
Name of the persistent organic pollutant (POP): -

#### Regulation (EU) 2019/1148 (marketing and use of explosives precursors)

Not listed/not relevant.

#### Regulation (EU) 649/2012 (PIC)

Not listed/not relevant.  
Chemicals qualifying for PIC notification: -

#### National regulations

Observe in addition any national regulations!  
Germany:  
TRGS 400 (Risk assessment for activities involving hazardous substances)  
TRGS 500 (Protective measures)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Colour Intensifier

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

TRGS 510 (Storage of hazardous substances in non-stationary containers)

TRGS 555 (Working instruction and information for workers)

### Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

### Other regulations, restrictions and prohibition regulations

#### Switzerland

#### VOCV-Regulation

Maximum VOC content (Switzerland) : 87,4 Weight-% according to VOCV

## 15.2 Chemical Safety Assessment

For this substance/mixture a chemical safety assessment has not been carried out.

## 15.3 Additional information

## SECTION 16: Other information

### 16.1 Indication of changes

07. Hints on joint storage - Storage class

### 16.2 Abbreviations and acronyms

ABC-Pulver	Extinguishing powder for fire class A, B and C
ABEK-P1	combination filter
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AVV	Abfallverzeichnis-Verordnung (Waste Regulation)
AWSV	Ordinance on facilities for the handling of substances hazardous to water
BGR	BG rules and regulations
ca.	circa
CAS	Chemical Abstracts Service
CLP	classification, labelling and packaging
CMR	Carcinogen, mutagen or toxic for reproduction
DIN	German Institute for Standardization
DNEL	Derived No-Effect Level
EAK/EWC/EAC/CWR/CER	European Waste Catalogue
EC50 / CE50	Effective Concentration 50%
EG / EC / CE	European Community
EN	European Standard
EUH	supplemental hazard statement of the european union
GefStoffV	Gefahrstoffverordnung (Hazardous Substances Ordinance)
GHS / SGH	Globally Harmonised System
H-Sätze	hazard statements
IATA-DGR	International Air Transport Association-Dangerous Goods Regulations
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization-Technical Instructions
IMDG-Code	International Maritime Dangerous Goods Code
ISO	International Organization for Standardization
LC50 / CL50	Lethal Concentration 50%
LD50 / DL50	Lethal Dose 50%
log P O/W	Partition coefficient n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (marine pollution)
NOAEL (DSET)	No observed adverse effect level
NOEC (CSEO)	No observed effect concentration

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Colour Intensifier

Revision date : 12.08.2022

Version (Revision) : 5.2.1 (5.2.0)

Print date : 11.12.2023

---

Nr.	Number
OECD	Organisation for Economic Co-operation and Development
PBT	persistent, bioaccumulative and toxic
pH	Potentia hydrogenii
PIC	prior informed consent
PNEC	Predicted No-Effect Concentration
POP	Persistent organic pollutants
P-Sätze	precautionary statements
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	International Carriage of Dangerous Goods by Rail
STEL / LECT	short-term exposure limit
TRGS	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
TWA / MPT	time-weighted average
UN/ONU	United Nations
VOC/COV/VOS/LZO	Volatile Organic Compound
VOCV	Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)
vPvB	very persistent and very bioaccumulative
WGK	Wassergefährdungsklasse (Water hazard class)

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

### 16.3 Key literature references and sources for data

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL  
ECHA: Registered substances (<https://echa.europa.eu/information-on-chemicals/registered-substances>)  
REACH Article 59: Candidate List of substances of very high concern for Authorisation  
(<https://echa.europa.eu/candidate-list-table>)

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard statements for physical hazards : On basis of test data.  
Hazard statements for health hazards : Calculation method.  
Hazard statements for environmental hazards : Calculation method.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### 16.6 Training advice

None

### 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data

# Safety Data Sheet

( EN / D )

according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 12.08.2022

**Version (Revision) :** 5.2.1 (5.2.0)

**Print date :** 11.12.2023

---

sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

( EN / D )